

NEC X551UHD

Order Code: X551UHD

NEC LCD 55" Professional Large Format Display



NEC is ushering in a new era of visual experience with NEC X551UHD. The display sets new standards in image quality by providing a 55 inch (139.7 cm) canvas with Ultra High Definition (UHD) guaranteed to capture undivided attention of spectators and viewers. Loaded with innovative features and high end components, this model delivers a complete package for all kinds of demanding professional applications.

This display is ideal for any heavy duty application from control rooms to CAD/CAM, from medical review to professional conferencing, from creative multimedia design to life size digital signage.

BENEFITS

Stunning "pixel-free" ergonomic viewing - delivered by an Ultra High Definition (3,840 x 2,160) Professional LED backlit S-IPS panel.

Enhanced imaging performance - advanced settings of all relevant visual parameters for full control of brightness, colour, gamma and uniformity via Spectraview Engine.

Reliable colour reproduction - due to 10-bit colour performance with amazing viewing angles and hardware calibratable LUT for accurate image presentation.

Mission-critical 24/7 ready operation - with reliable, industry grade components and NEC trusted performance.

Flexible multi-source conferencing and efficient split-screen operation - featuring a wide future-ready range of digital connectivity.

Future Ready with OPS Cable Free Expansion - upgrade the power of your display at any time without the need for external cables or devices.

Perfectly Scaled - content with lower resolution (e.g. FullHD) can be upscaled to UHD by a bi-cubic 4x4 pixel interpolation algorithm to achieve smooth colours and clear edges.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.

4K UHD

NEC Factory Preset
DICOM
SIMULATION



NaViSet
Administrator 2

NEC X551UHD - Technical Specification

DISPLAY	Panel Technology	S-PVA with Edge LED backlights
	Active Screen Area (W x H) [mm]	1,209.06 x 680.4
	Screen Size [inch/cm]	54.6 / 138.68
	Brightness [cd/m ²]	500, 400 (Typical)
	Contrast Ratio (typ.)	4,000:1
	Viewing Angle [°]	178 horizontal / 178 vertical (typ. at contrast ratio 10:1)
	Response Time (typ.) [ms]	6 (grey-to-grey)
	Haze Level [%]	10
	Supported Orientation	Landscape; Portrait
SYNCHRONISATION RATE	Horizontal Frequency [kHz]	31.5 - 91.1 (analog and digital)
	Vertical Frequency [Hz]	50 - 85
RESOLUTION	Native Resolution	3840 x 2160 at 60 Hz
	Supported on DisplayPort and HDMI	3840 x 2160 (60 Hz); 3840 x 2160 (24/30 Hz); 1920 x 1080; 1600 x 1200; 1360 x 768; 1280 x 1024; 1280 x 768; 1080i; 1080p; 1024 x 768; 800 x 600; 720p (50/60 Hz); 640 x 480; 480p (60 Hz)
	Supported on HDMI only	4096 x 2160 (24 Hz); 3840 x 2160 (25 Hz); 1360 x 768; 576i (50 Hz); 480i (60 Hz)
CONNECTIVITY	Input Video Digital	1 x DisplayPort (with HDCP); 2 x DVI-D (with HDCP); 4 x HDMI (with HDCP)
	Input Audio Analogue	1 x 3.5 mm jack
	Input Audio Digital	1 x HDMI; DisplayPort
	Input Control	LAN 100Mbit; remote control wire (3.5mm jack); RS232
	Output Control	LAN 100Mbit
	Remote Control	LAN with SNMP; Remote Control IR (internal/external (optional) sensor); RS-232C (9-pin D-sub) Input
OPS OPTION SLOT	Slot Technology	Open pluggable specification (NEC / Intel OPS standard)
	Inrush Current [A]	max. 10
	Power Consumption [W]	max. 61
	Voltage / Current [V/A]	16/4
SENSORS	Ambient Light Sensor	Integrated, triggered actions programmable
	Human Sensor	Optional, external, 4-5m range, triggered actions programmable
	Temperature Sensor	Integrated, 3 sensors, triggered actions programmable
	NFC Sensor	Integrated, 2cm range, free NEC Android App required
ELECTRICAL	Power Consumption [W]	100 Eco (shipment setting), 200
	Power Savings Mode [W]	< 0.5 (ECO Standby); < 2.5
	Power Management	VESA DPMS
ENVIRONMENTAL CONDITIONS	Operating Temperature [°C]	+0 to +40
	Operating Humidity [%]	20 to 80
MECHANICAL	Dimensions (W x H x D) [mm]	Without stand: 1,250.2 x 721.0 x 78.1
	Weight [kg]	Without stand: 28.7
	Bezel Width [mm]	18.5
	VESA Mounting [mm]	4 holes; 400 x 400 (FDMI); M8
ADDITIONAL FEATURES	Special Characteristics	Carbon footprint meter; DICOM support; NaViSet Administrator 2
	Safety and Ergonomics	C-tick; CE; FCC Class B; PSB; RoHS; TÜV GS; UL/C-UL or CSA; VCCI
	Audio	Integrated Speakers (10 W + 10 W); Optional Speakers (15 W + 15 W)
	Shipping Content	CD-ROM (User Guides/Manuals); Display; DisplayPort Cable; Power Cable; Remote Control
	Warranty	3 years conditional warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension
	Operating Hours	24/7
AVAILABLE OPTIONS	Accessories	Speaker (SP-RM1, SP-55SM); Wall mounts (MTM1U, LSM1U, LTM1U, MSM1U, MTA1U, LTA1U, MTMP1U)
	OPS	HD-SDI 1.5G,3G; HDBaseT receiver; Intel® Atom, Celeron and Core CPUs
GREEN FEATURES	Energy Efficiency	Ambient light sensor; Annual energy consumption: 146 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: A+; Human Sensor
	Ecological Materials	Manuals on CD; Optional feet

For more information, visit au.nec.com, email contactus@nec.com.au or call 131 632

Australia
NEC Australia Pty Ltd
au.nec.com

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

North America (USA)
NEC Corporation of America
www.necam.com

Asia Pacific (AP)
NEC Asia Pacific
sg.nec.com

Europe (EMEA)
NEC Enterprise Solutions
www.nec-enterprise.com

X551UHD | v.09.05.2016

NEC Australia Pty Ltd reserves the right to change product specifications, functions, or features, at any time, without notice. Please refer to your local NEC representatives for further details. Although all efforts have been made to ensure that the contents are correct, NEC shall not be liable for any direct, indirect, consequential or incidental damages resulting from the use of the equipment, manual or any related materials. The information contained herein is the property of NEC Australia Pty Ltd and shall not be reproduced without prior written approval from NEC Australia Pty Ltd.

Copyright © 2016 NEC Australia Pty Ltd. All rights reserved. NEC, NEC logo, and UNIVERGE are trademarks or registered trademarks of NEC Corporation that may be registered in Japan and other jurisdictions. All other trademarks are the property of their respective owners. All rights reserved. Printed in Australia. Note: This disclaimer also applies to all related documents previously published.

Orchestrating a brighter world

NEC