

MultiSync® E557Q

LCD 55" Essential Large Format Display

Datasheet



Enter the world of digital signage

You can now enjoy all the benefits of an NEC display while keeping your price-conscious approach to spending. The E Series is the perfect introduction to the world of professional digital signage. Bring NEC's renowned performance and dependable quality into your meeting room or retail space and see just how seamlessly it will meet your digital signage needs.

The E Series impressively displays your retail content and is easy enough to use in daily meetings. You'll enjoy the MediaPlayer's native UHD content playback - which can be used automatically via the integrated playback tool. The 10W powered USB interface that lets you power external devices like the Raspberry Pi to upgrade the computing power of the display. For instant meeting start-ups, the display comes equipped with auto wake-up, which wakes up the screen once a notebook is connected. The NaViSet Administrator 2 is engineered to provide remote support, supporting E Series displays from 7th generation onwards.

Benefits

Reduced Installation and Operating Costs - highly energy efficient LED backlit display ensures low power consumption, longer backlight lifetime and lighter design for easy transportation, mounting and integration.

Slim Design and Integrated Speakers - the aesthetic design is pleasing to the eye and enables easy, low cost installation.

Future Ready Connectivity - featuring multiple industry standard digital and analogue signal inputs for flexible integration into AV infrastructures.

Standalone operation - the display is designed for straightforward standalone operation due to integrated USB media player, speakers and scheduling functionality.

Effortless content playback - the integrated USB media player supports various image video file formats for effortless and standalone content playback.

Product Information

| | |
|---------------|--|
| Product Name | MultiSync® E557Q |
| Product Group | LCD 55" Essential Large Format Display |
| Order Code | 60004552 |

Display

| | |
|---------------------------------|---|
| Panel Technology | VA with Direct LED backlights |
| Active Screen Area (W x H) [mm] | 1,210 x 680 |
| Screen Size [inch/cm] | 54.6 / 139 |
| Aspect Ratio | 16:9 |
| Pixel Pitch [mm] | 0.315 |
| Brightness [cd/m ²] | 350 |
| Contrast Ratio (typ.) | 4000:1 |
| Viewing Angle [°] | 178 horizontal / 178 vertical (typ. at contrast ratio 20:1) |
| Response Time (typ.) [ms] | 8 |
| Panel Refresh Rate [Hz] | 60 |
| Haze Level [%] | Standard (2) |
| Supported Orientation | Landscape |

Synchronisation Rate

| | |
|----------------------------|----------|
| Horizontal Frequency [kHz] | 15 - 134 |
| Vertical Frequency [Hz] | 23 - 70 |

Resolution

| | | | | |
|------------------------|--|---|---|--|
| Native Resolution | 3840 x 2160 | | | |
| Supported Resolutions | 3840 x 2160; 1920 x 1080; | 1280 x 1024; 1280 x 800; | 1280 x 720; 1024 x 768; | 800 x 600; 640 x 480 |
| Supported on HDMI only | 1080p (60 Hz); 1080p (30 Hz); 1080p (24 Hz); | 1080p (0 Hz); 1080i (50 Hz); 1080i (60 Hz); | 720p (60 Hz); 720p (50 Hz); 576p (50 Hz); | 576i (50 Hz); 480p (60 Hz); 480i (60 Hz) |

Connectivity

| | |
|-----------------------|--|
| Input Video Analogue | 1 x VGA; Component (RCA); Composite (RCA) |
| Input Video Digital | 3 x HDMI |
| Input Audio Analogue | 1 x 3,5 mm jack |
| Input Audio Digital | 3 x HDMI |
| Input Control | LAN 100Mbit; RS232 |
| Output Audio Analogue | 1 x 3,5 mm jack |
| Output Audio Digital | 1 x SPDIF |
| Remote Control | Remote Control IR; RS-232C (9-pin D-sub) Input |

Sensors

| | |
|----------------------|--|
| Ambient Light Sensor | Integrated, triggered actions programmable |
|----------------------|--|

Electrical

| | |
|--------------------------------|---------------------|
| Power Consumption Eco/max. [W] | 110 shipping |
| Power Savings Mode [W] | < 0.5 (ECO Standby) |

Environmental Conditions

| | |
|----------------------------|------------|
| Operating Temperature [°C] | +0 to +40 |
| Operating Humidity [%] | 10 to 80 |
| Storage Humidity [%] | 5 to 85 |
| Storage Temperature [°C] | -10 to +60 |

Mechanical

| | |
|-----------------------------|---|
| Dimensions (W x H x D) [mm] | Without stand: 1,239 x 712 x 79 |
| Weight [kg] | Without stand: 15 |
| Bezel Width [mm] | 12.9 (left, right and top); 14.7 (bottom) |
| VESA Mounting [mm] | 4 holes; 400 x 200 (FDMI); M6 |

MediaPlayer

| | |
|--------------------------------------|--|
| Supported File Storage / File System | USB 2.0 / FAT16, FAT32 |
| Supported Image Formats | JPG (baseline, progressive, RGB, CMYK); max. resolution 15360 x 8640 |
| Supported Audio Formats | MP3 (MP3); max. bit-rate 320 kBit/s |
| Supported Video Container Formats | MPG, MPEG, MPEG2-TS, MPEG2-PS, MP4, MKV, AVI, Motion JPEG |
| Supported Video Codecs | MPEG1 , MPEG2, H.263, H.264, H.265, WMV |
| Supported Audio Codecs (Video) | LPCM, MP3, AC-3, AAC, WMA Standard, WMA 9 Professional |

Available Options

| | |
|-------------|---|
| Accessories | Feet (ST-43E); Trolley (PDMHM-L); Wall mount (PDW S 32-55L) |
|-------------|---|

Green Features

| | |
|----------------------|--|
| Energy Efficiency | Annual energy consumption: 151 kWh (based on 4 operating hours per day); ECOMode; Energy efficiency class: A; LED backlight; Low power consumption |
| Ecological Standards | EnergyStar 8.0 |

Additional Features

| | |
|-------------------------|---|
| Special Characteristics | Ambient Light Sensor; Audio settings with equalizer; CEC Support; Colour temperature mode; Crestron RoomView Support; Display Browser Control; Energy saving picture mode; HDMI with UHD at 60 Hz; HDR Gamma Support (HLG, PQ); Mac and Windows compatible; NaViSet Administrator 2; Powered USB-Port; Retail picture mode; Scheduler; SNMP Support; USB Media Player |
| Colour Versions | Black Front Bezel, Black Back Cabinet |
| Safety and Ergonomics | EMC Class B; FCC; PSB; RCM; TÜV S; UL/C-UL; VCCI |
| Audio | Integrated Speakers (10 W + 10 W) |
| Shipping Content | Display; HDMI Cable; Power Cable; Remote Control |
| Warranty | 3 years warranty incl. backlight |
| Operating Hours | 16/7 |



RCM



VCCI

This document is © 2020 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 08.10.2020

* Model subject to availability in your region.

For, more information contact:

Display Square

+971 4 3300429

info@displaysquare.com | www.displaysquare.com

Copyright © 2020 Display Square All rights reserved. Specifications and designs are subject to change without notice.
Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Display Square is not liable for errors or omissions.
All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

DISPLAY SQUARE