

MultiSync® V554-T (Infrared Touch) LCD 55" Infrared Touch Display

Datasheet



Interactive Digital Signage goes plug and play

The interactive touch NEC MultiSync® V554-T display delivers a satisfying user experience with fast and precise touch performance. Even in high bright conditions the display demonstrates strong light resistance to maintain high reliability and accuracy. It's swift and smooth touch response is ideal for kiosk, wayfinding or self-order applications thanks to an improved touch and writing performance. Supporting both single and multi-user applications, usage is versatile with 10 simultaneous touch points. Crisp and clear images and readability from different viewing angles and distances are guaranteed by combining brightness levels of 440 cd/m² with the anti-reflective and super robust glass surface.

The interactive 55" display is designed for retail, hospitality and transportation use to take orders, assist shoppers and guide travellers. In corporate meeting areas and education the V554-T is ideal for creative huddle spaces, to train students and personnel and provide instruction whilst tracking the growing trend of interactivity in our daily lives.

Benefits

Inspiring touch performance boosts user experience - the fast, stable and robust touch performance supports up to 10 touch points.

Resilient and durable design - the 4mm thermal tempered protective glass with single sided anti-glare coating withstands vandalism and ensures perfect readability with reduced reflection and minimal visibility of finger prints.

Simple Plug & Play - easy set-up without the need to install any drivers on the host PC for all major operating systems.

Operational safety even in bright environments - the strong light resistance provides high reliability and accuracy even under difficult, brightly-lit conditions.

Mission-critical 24/7 ready operation - the meticulous selection of industrial-grade components and careful design focused on demanding usage scenarios accompany an impressive and continuous viewer experience.

Future Ready with Open Modular Intelligence Expansion - upgrade the power of your display at any time by seamlessly integrating one of NEC's options for OPS Slot-in PCs, Raspberry Pi compute modules or signal interfaces for content feed and computing.

Cost Saving Device Management - save effort whilst managing all connected NEC devices from a centralised location by using the NaViSet Administrator 2 software tool.

Product Information

Product Name	MultiSync® V554-T (Infrared Touch)
Product Group	LCD 55" Infrared Touch Display
Order Code	60004356

Display

Panel Technology	S-IPS with Edge LED backlights
Active Screen Area (W x H) [mm]	1,209.6 x 680.4
Screen Size [inch/cm]	55 / 138.8
Brightness [cd/m ²]	440
Contrast Ratio (typ.)	1200:1
Viewing Angle [°]	178 / 178 (at contrast ratio > 10:1)
Colour Depth [bn]	1.073 (10bit)
Response Time (typ.) [ms]	8 (grey-to-grey)
Haze Level [%]	Pro (44)
Supported Orientation	Face Up; Landscape; Portrait

Synchronisation Rate

Horizontal Frequency [kHz]	31.5 - 91.1 (analog and digital)
Vertical Frequency [Hz]	24 - 85

Resolution

Native Resolution	1920 x 1080			
Supported Resolutions	4096 x 2160; 3840 x 2160; 1920 x 2160; 1920 x 1200; 1920 x 1080;	1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1366 x 768;	1360 x 768; 1280 x 1024; 1280 x 960; 1280 x 800; 1280 x 720;	1024 x 768; 800 x 600; 640 x 480

Connectivity

Input Video Analogue	1 x VGA
Input Video Digital	1 x DVI-D (with HDCP); 2 x DisplayPort (with HDCP); 2 x HDMI (with HDCP)
Input Audio Analogue	2 x 3,5 mm jack
Input Audio Digital	2 x DisplayPort; 2 x HDMI
Input Control	1 x LAN 100Mbit; 1 x Remote Control (3.5 mm jack); 1 x RS232
Input Data	1 x microSD (MediaPlayer); 1 x USB 2.0 (MediaPlayer); 1 x USB 2.0 (Service); 1 x USB Type-B (Upstream); 2 x USB 2.0 (Compute Module, 1 x 5V/2A powered)
Output Video Digital	1 x DisplayPort (loop through: DisplayPort, OPS slot-in PC)
Output Audio Analogue	1 x 3,5 mm jack
Output Control	1 x LAN 100Mbit

Open Modular Intelligence

OPS Slot	Slot Technology: Open pluggable specification (NEC / Intel OPS standard)
OPS Max. Current / Power Consumption [A / W]	10 / 61
Compute Module Slot	Slot Technology: Compute Module Slot (NEC proprietary standard)

Sensors

Ambient Light Sensor	Integrated, triggered actions programmable
----------------------	--

Human Sensor	Optional, external, 4-5m range, triggered actions programmable
Temperature Sensor	Integrated, 3 sensors, triggered actions programmable
NFC Sensor	Integrated, 2cm range, free NEC Android App required

Electrical

Power Consumption Eco/max. [W]	110 Eco (shipment setting), 150
Power Savings Mode [W]	< 0.5 (ECO Standby); < 3 (Networked Standby)
Power Management	VESA DPMS

Environmental Conditions

Operating Temperature [°C]	+0 to +35
Operating Humidity [%]	20 to 80

Mechanical

Dimensions (W x H x D) [mm]	1,278.6 x 749.4 x 85.9
Weight [kg]	39
Bezel Width [mm]	33.4 (left and right); 33.4 (top and bottom)
VESA Mounting [mm]	300 x 300 (FDMI); 4 holes; M6
Ingress Protection	IP5X (front); IP2X (back)

Glass

Thickness [mm]	4
Type	Thermal-tempered, anti-glare coating
Light Transmission [%]	88 (+/- 1 %)

Touch

Touch Technology	Infrared Touch
Number of Touches	Real multi-touch up to 10 touches
Response Time [ms]	≤ 15
Touch Method	Finger; Gloves; Stylus (≥ 6 mm)
Supported Operating System	Android; Linux; Mac OS; Raspberry Pi; Windows
Data Interface	USB-HID
Touch Resolution	32767 x 32767

MediaPlayer

Supported File Storage / File System	MicroSDHC / FAT16, FAT32; USB 2.0 / FAT16, FAT32
Supported Image Formats	JPG (baseline, progressive, RGB, CMYK); max. resolution 5000 x 5000; PNG (interlace, alpha channel); max. resolution 4000 x 4000
Supported Video Formats	MP4 / MOV / FLV (video H.264, audio MP3, AAC); max. resolution 1080p at 30 Hz, 1080i at 60 Hz; MPG (video mpeg1/2, audio mpeg audio layer2/3, AAC-LC); MP @ ML, MP @ HL; WMV (video H.264, wmv advanced L3, wmv simple / main, audio mp3 wmv std); max. resolution 1080p at 30 Hz, 1080i at 60 Hz
Supported Audio Formats	MP3 (MP3); max. bit-rate 320 kBit/s; WAV (LPCM); max. 48 kHz sampling

Available Options

Accessories	Feet (ST-401); Speaker (SP-TF1); Trolley (PDMHM-L, PD02MHA, PD03MHA); Wall mount (BalanceBox 400 MEDIUM, PD02WHM, PDW S 32-55 L and P, PD02W T L L, PD03W T M P)
Compute Module Slot	NEC Compute Module; Raspberry Pi Compute Module 1 and 3

OPS Slot HD-SDI 1.5G, 3G; HDBaseT receiver; Intel® Atom, Celeron and Core CPUs; OPS-2C HDMI + DP Interface; OPS-2C Quad 3G SDI

Green Features

Energy Efficiency	Ambient light sensor; Annual energy consumption: 175 kWh (based on 4 operating hours per day); Carbon savings meter; ECOMode; Energy efficiency class: B; Human Sensor
Ecological Materials	Manuals on CD; Optional feet

Additional Features

Special Characteristics	Ambient Light Sensor; AMX NetLinx Support; ASCII Control Commands; Auto ID assignment; Auto tiling function; Automated Email Alert; CEC Support; Crestron RoomView Support; DICOM Simulation; Display Browser Control; Emergency Notification; Full System Scheduler; Hardware colour calibration possible; Image flip; Intelligent Wireless Data (based on NFC); KeyGuide; MediaPlayer with Browser Control; NaViSet Administrator 2; OmniColor Control; OSD rotation for portrait mode; PJLink Support; Point Zoom Function; Powered USB-Port; Programmable 12-bit LUT with 3 memory banks; Removable Logo; Secure Mode Operation; Slim LED Indicator; SNMP Support; TileMatrix (10 x 10); User readable log function; Various picture in picture options
Colour Versions	Black Front Bezel, Black Back Cabinet
Safety and Ergonomics	C-tick; CE; EAC; EMC Class B; FCC; PSB; RoHS; SASO; TÜV GS; UL/C-UL; UL/C-UL or CSA; VCCI
Audio	Integrated Speakers (10 W + 10 W); Optional Speakers (15 W + 15 W)
Shipping Content	CD-ROM (User Guides/Manuals); Display; DVI-D cable; Power Cable; Remote Control; USB cable; User Manual
Warranty	3 years warranty incl. backlight; additional services available; optional 4. + 5. year warranty extension
Operating Hours	24/7



CE



C-tick



RoHS



TÜV GS



VCCI

This document is © 2020 NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 11.10.2020

* Model subject to availability in your region.

For, more information contact:

Display Square

+971 4 3300429

info@displaysquare.com | www.displaysquare.com

DISPLAY SQUARE

Copyright © 2020 Display Square All rights reserved. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Display Square is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.